



Fleet Motor Oil

PureGreen® Fleet Motor Oil is a premium, heavy-duty engine oil formulated with premium re-refined base oils and a high-performance additive system that includes ashless dispersants, detergents, oxidation and corrosion inhibitors, anti-wear and anti-foam agents. These characteristics provide ongoing engine cleanliness, outstanding soot control, superior wear protection and extended engine life.

PureGreen Fleet Motor Oil conserves irreplaceable petroleum resources, protects the environment and delivers lubricant performance equal to or greater than top conventional oils.

PureGreen Fleet Motor Oil is formulated to provide:

- Superior wear protection
- Protection from varnish deposits and sludge formation
- Excellent rust and bearing corrosion protection
- Resistance to foaming
- Low ash content to minimize deposits and keep intake ports clean

PureGreen Fleet Motor Oil is recommended for use in mixed fleets operating under severe service and subjected to a wide range of operating conditions. It is designed for use in high output 2-stroke cycle diesel engines and both turbocharged and naturally aspirated diesel and gasoline engines (SJ performance) in automotive, heavy-duty trucking, construction, marine, mining and farm applications. PureGreen Fleet Hydraulic SAE 10W is recommended for use in hydraulic systems and hydrostatic transmissions in Caterpillar and other off-highway heavy equipment when a premium product is desired. PureGreen Fleet SAE 30W is recommended for use in powershift transmissions requiring a Caterpillar TO-2 or Allison C-4 performance level.

Meets API- CF-2 (SAE 30W & 40W), CF, CE, CD-II, CD, SJ (SAE 30W & 40W), SH, SG

Meets Performance Requirements for- Detroit Diesel Type 1 & 2, Allison C-4 Fluid (SAE 30W), Caterpillar CD/TO-2 Fluid, Man 270, MIL-L-2104E & MIL-L-46152D (SAE 30W)

PureGreen Fleet Motor Oil **TYPICAL INSPECTION TESTS**

SAE Grade	10W	30W	40W	50W
API Service	CF	CF-2	CF-2	CF
API Gravity	30.5	29.0	28.5	28.3
Flash Point, °F	405	430	428	432
Pour Point, °F	-25	-30	-27	-27
cSt @ 40°C	41.2	95.5	154	207
cSt @ 100°C	6.2	10.5	14.8	18.0
Viscosity Index	106	102	100	97
Total Base Number	8.1	8.4	8.4	8.4
Sulfated Ash, wt %	.96	1.00	1.00	1.00
Re-Refined Base Oil, %	>75	>75	>75	>75