

PureGreen

Hydraulic AW Oil

PureGreen® Hydraulic AW Oils are premium hydraulic fluids formulated from select re-refined base stocks and advanced additive technology to deliver ultimate equipment protection. They offer the unique combination of optimum equipment protection and the conservation of irreplaceable petroleum resources.

PureGreen Hydraulic AW Oils are excellent anti-wear oils containing anti-oxidation, anti-corrosion, anti-rust and anti-foam agents. These superior characteristics protect pumps, lines and controls against rust and corrosion. They also exhibit excellent demulsification (water separation) properties, even at high operating temperatures.

PureGreen Hydraulic AW Oils deliver performance equal to or greater than top conventional lubricants. They are recommended for hydraulic systems, high-pressure circulating systems, and are suitable for use where the following requirements are recommended: Denison HF-O, HF-1 & HF-2, Sperry Vickers M-2950-S & I-286-S, Cincinnati Milacron P-68, P-69, and P-70.

PureGreen Hydraulic AW Oil **TYPICAL INSPECTION TESTS**

ISO Grade	32	46	68
Lbs./Gallon	7.2	7.2	7.2
Pour Point °C	-27	-22	-22
Flash Point, °C	200	200	210
Oxidation Hrs, ASTM D-943	>2500	>2500	>2500
Viscosity Index	101	101	101
Viscosity cSt @ 40°C	32.0	45.8	68.2
Viscosity cSt @ 100°C	5.6	6.9	9.1
Gravity, API	30.4	31.8	31.1
Re-Refined Base Oil, %	>90	>90	>90