

PureGreen

Multi-Purpose Automatic Transmission Fluid

PureGreen® MP ATF is a premium transmission fluid designed and recommended for use in automatic transmissions in passenger cars, SUV's and light trucks previously serviceable by GM DEXRON®-III (H) and Ford MERCON® brands. It may also be used in equipment requiring a "Type A" ATF fluid, Allison C-4, Caterpillar TO-2, and Ford specifications M2C138-CJ and M2C166-H.

PureGreen MP ATF is formulated to provide:

- Superior wear protection
- Excellent frictional properties for smooth shifting
- Excellent anti-shudder performance
- Good seal compatibility
- Protection against varnish and sludge formation
- Superior thermal stability and oxidation resistance
- Outstanding low-temperature performance

Formulated with select re-refined base stocks, PureGreen MP ATF delivers the unique combination of environmental responsibility and ultimate lubricant performance. PureGreen MP ATF's state-of-the-art additive system and premium base stocks provide protection and performance equal to any top conventional transmission fluid while conserving irreplaceable petroleum resources and delivering tangible environmental benefits.

PureGreen MP ATF is not recommended for use in transmissions requiring GM DEXRON®-VI, Ford MERCON®-V and MERCON® SP fluids.

PureGreen Multi-Purpose ATF (D-III/M) **TYPICAL INSPECTION TESTS**

Density, g/cm ³ @ 15° C	0.860
Flash Point, COC C° (F°)	212 (413)
Viscosity, cP @ -20° C	1300
Viscosity, cP @ -30° C	4200
Viscosity, cP @ -40° C	17000
Viscosity, cSt @ 40° C	35.4
Viscosity, cSt @ 100° C	7.2
Viscosity Index	172
Pour Point, C° (F°)	-52 (-61)
Color	Red
Foam Test, ASTM D892	Pass
Re-Refined Base Oil, %	>50