



## ***Universal Tractor Fluid***

PureGreen® Universal Tractor Fluid is formulated from premium re-refined base stocks and state-of-the-art additive technology. It is designed for use in a variety of farm equipment, off-highway machinery, industrial tractors, final drives, power take-off units, wet brakes, power steering units and hydraulic systems. It provides the unique combination of ultimate equipment protection and environmental conservation.

The combination of special friction modifiers and shear-stable viscosity modifiers offer a supreme performance level. PureGreen Universal Tractor Fluid is suitable for use in all major OEM equipment including but not limited to Kubota, Oliver, Minneapolis-Moline, International Harvester, White Farm, John Deere, Deutz-Allis Chalmers, Ford-New Holland, J.I. Case, and Massey Ferguson. This new and improved fluid offers the convenience of using one tractor fluid in place of two or more fluids while maintaining optimum component performance and durability.

PureGreen Universal Tractor Fluid conserves irreplaceable petroleum resources and delivers performance equal to or greater than top conventional products. It is recommended for use where the following performance specifications are required:

*John Deere- Quatrol, J20A, J20C, J21A, Hy-Gard J14B/C, Type 303*

*International Harvester- Hy-Tran, B-6*

*Massey Ferguson- M-1110, M-1127B, M-1129A, M-1135, M-1141*

*Allis Chalmers- Power Fluid 821 XL*

*J.I. Case- TFD (JIC-143/146), Hi-Vis (JIC-185), JIC-144/145, MS-1204, MS1205/1206/1207, MS-1210 (TCH) and B-6*

*Ford New Holland- M2C86-A/B/C, M2C134-A/B/C/D, M2C41-B, M2C43, M2C53-A/B, M2C92-A*

*Vickers- I-2986-S*

*Kubota Universal Transdraulic Fluid- UTD*

### ***PureGreen Universal Tractor Fluid*** **TYPICAL INSPECTION TESTS**

API Gravity @ 60° F	30.3
Lbs./gallon	7.2
Viscosity, cPs @ 100°C	9.6
Viscosity, cPs @ 40°C	54.4
Viscosity Index	119
Pour Point, °C	-35
Flash Point, °C	218
Re-Refined Base Oil, %	>90